

Epoca Classic

Product Description



ege

THE URGE TO EXPLORE SPACE

Product description	Methods	Product data
Construction characteristics		
Structure	ISO 2424	Tufted loop pile
Gauge	ISO 2424	5/32
Pile material	DIR 96/73, 96/74	100% polyamide
Fibre	Brand owner's	
Coloration	-	Continuous dyed
Backing	eTL	CL - Contract latex
Dimensions	CEN/TS 14159	Approx. 400 cm
Total thickness	ISO 1765	Apr 7,5 mm.
Surface pile thickness	ISO 1766	Apr 3,0 mm.
Tufts	ISO 1763	Apr 85.000 pr.m2
Total carpet weight	ISO 8543	Apr 2.450 g/m2
Pile yarn weight	eTL	590 g/m2
Surface pile density	ISO 8543.	Apr 0,120 g/cm3
Soil protection	eTL	Yes

Performance characteristics

Performance areas	EN 1307	Class 33 - Commercial - Heavy
Guarantee	eTL	Contract certificate
Performance areas	Gulvbranchen	Class 33
Castor chair suitability	EN 985	Intensive use
Suitability for use on stairs	EN 1963	Yes
Static control	eTL	Permanently antistatic
Body walking test	EN 1815	Antistatic
Acou.insu. from impact noise	ISO 717-2	31 dB
Acoustical absorption	ISO 354	0,25 aW
Suitability underfloorheating	eTL	Apr 0,13 m2K/W
Light reflectance	eTL	Testreport
Colour fastness to light	ISO 105-B02	>5
Colour fastness to rubbing wet	ISO 105-X12	>3
Colour fastness to rubbing dry	ISO 105-X12	>3-4
Colourfast. to water patterned	ISO 105-E01	>4

Safety & Environment

Fire classification	MK GODKENDELSE	Approved
	DIBT AbZ.no.	Z-156.601-439
	VKF/AEAI	Approved
	EN 13501-1 Euroclass	Cfl-s1
	China	Cfl-s1-t1
	ASTM E 662	Approved
	EN 14041	Certified
CE Labeling	CPR	1021-CPR-007-2/16
	Declaration of Performance	DOP 2C-PA-Foam
	Notified body no.	1021
	Ce Year	07
	Content of PCP EN 12673	DL
	Formaldehyde emission	NA
	Slip resistance EN 13893	Class DS

Product description	Methods	Product data
Indoor climate	DIM certificate	No. 005
	INSTA 800	Dust level 5
	BASTA	Registered
	Green Label Plus	Approved
	Emissions dans l'air intérieur	A+/A+
	GECA	Approved
Environment	Byggvarudeklaration	eBVD

Guides

Installation + adhesive guide	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais
Cleaning, stain removal	DK	Dansk
	N	Norsk
	S	Svensk
	GB	English
	D	Deutsch
	F	Francais

Manufacturer characteristics

Factory certification	ISO 9001	Audited and verified by BVC
	ISO 14001	Audited and verified by BVC
	EMAS	Audited and verified by BVC
	DS/OHSAS	Audited and verified by BVC
	DS 49001	Audited and verified by BVC
	CRuk	Member of Carpet Recycling UK
	TransQ	Qualified

ege

THE URGE TO EXPLORE SPACE